

WGA-21002g Large Display



WGA-21002g standard layout „blue PV-symbols“



35m



1000x700x56mm



Indoor use



Outdoor use
(optional)

Display for indoor or outdoor use,

With 2 values (4/6 digits), free choice of units and text

Height of digits: 100mm, readable up to 35m

Display technique: LCD yellow, 1x4 and 1x6 digits, transfective, maintenance-free back lighted, With 7 segments

Front panel: Coloured front picture “blue PV-symbols”

Housing: Aluminium black powder-coated, measures (BxHxT): 1000x700x56mm (Housing for outdoor use, please see list of options)

Power supply: 12VDC (power supply incl.)

Interface: RS 232, RS 485 or impulse input.

Power displayed

kW, 4 digits, 0-99,99 kW

W, 4 digits, 0-9999 W

Values displayed

Actual power, energy total

Interface

Impulse standard (e.g. counter or WebLog)

RS 232 (for SMA Control, Fronius Card/Box)

RS 485 (for SMA Webbox – you need an adapter additionally! Sputnik 485 or SolarLog)

Options for WGA-21002g

Variants of housings

Housing aluminium, stainless steel, showcases, wall housing up to 4m²

Housing for outdoor use

Front design

Customized layout, English, French, Italian, or Spanish version

Date of issue 11/2010

- specifications subject to change without notice -

Weigel Meßgeräte GmbH

Postfach 720154 D-90241 Nürnberg Telefon: 0911 / 42347-0
Erlenstraße 14 D-90441 Nürnberg Telefax: 0911 / 42347-39
Vertrieb: 0911 / 42347-94
Internet: <http://www.weigel-messgeraete.de>
e-mail: vertrieb@weigel-messgeraete.de

